



IMPORTANT WARRANTY INFORMATION

REGISTER YOUR WARRANTY ON-LINE AT
WWW.PEBBLETEC.COM



LICENSED PEBBLE TEC®/PEBBLE SHEEN® POOL FINISH APPLICATOR

X MODERN METHOD GUNITE, INC.

Your pool's interior has just been surfaced with PEBBLE TEC®/PEBBLE SHEEN® brand pool finish, a long lasting and naturally beautiful finish. There are a few things we would like you to know to maintain your warranty, prevent stains and discoloration, and extend the life of your pool finish.

- DO NOT fill your pool with soft water. If any of your outside hosebibs are soft water, please notify your builder/applicator.
- DO NOT enter the pool until it is completely filled with water. (This also means pets.)
- We will return (usually within a few days) to clean the surface of the pebbles with a solution. This procedure will brighten the overall appearance by exposing the pebbles and removing some of the "milky" look.
- The natural beauty of the finish will not be seen until the pool is full of water, filtered and chemically balanced.
- During the PEBBLE TEC®/PEBBLE SHEEN® pool finish process, cement is washed away from the surface of the finish. This cement and water is sometimes left in the yard in a wooden box or container. A separate crew will return within a few days to remove the container and its contents.
- The finish consists of pebbles and cement and will vary in color, shades, consistency and exposure. This is the intended look, natural as a stream, lake or river bed. The color and beauty will vary throughout the day as the sunlight reflects from different angles.
- It is recommended that you periodically (approximately once per week) brush your PEBBLE TEC®/PEBBLE SHEEN® pool finish, especially in areas that accumulate debris and/or in areas with poor circulation as brushing will assist in keeping the surface clean.
- Pebbles will come loose during the curing process (usually in the first few weeks). It is normal to experience a small loss of pebbles for a short period of time after pool startups. Don't worry. There are approximately 42 million pebbles in your pool!

We recommend that you "balance" your pool water using the "Saturation Index." This system takes into account pH, alkalinity, water temperature, chlorine, and calcium hardness. We recommend that for the first 30 days pH and alkalinity be monitored regularly as they can directly affect the appearance of the surface. Keep in mind, based on your water source, you may need to add "muriatic acid" to your new pool 2 to 3 times per week during the first month. After 30 days, the pool should be checked 1 to 2 times per week and adjusted accordingly. If your finish is a darker color, particularly black, it is even more important that you follow these instructions. Do not chlorinate your pool until water is filtered and pH and alkalinity are acceptable. Chlorine is highly

WARRANTY VALIDATION CARD

Dear Pool Owner:

To activate your warranty, you must register with Pebble Technology, Inc within 30 days of pool completion. Please fill out the card below completely and return via mail or visit our website at www.pebbletec.com and click on "Register Warranty" to register online.

Owner's Name _____

Address _____

City _____ State TX _____ Zip _____

Bus. Phone _____ Home Phone _____

Pool Builder _____

Pool Finish Applicator Modern Method Gunite, Inc

Color of PEBBLE TEC®/PEBBLE SHEEN® _____

Spa Yes No

Date Pool Finish Installed _____ New Pool Remodeled

Overall, how would you rate your builder?

Excellent Good Fair Poor

Would you recommend your pool builder? Yes No

Comment _____

Are you pleased with the surface? Yes No

Would you recommend PEBBLE TEC®/PEBBLE SHEEN® pool finish to someone wanting a pool? Yes No

Comment _____

What features of this product were most important to you?

(Please rank #1 as the most important.)

___ Appearance ___ Durability ___ Maintenance ___ Warranty

Comment _____

How did you hear about us?

Referral Radio Newspaper Pool Salesman

Is this the first pool you have owned? Yes No

Your age group is: 20-35 36-45 46+

I acknowledge I have read the attached sheet

X _____

reactive and can cause metals or minerals to precipitate (cloud water, scale and/or stain). A number of retail stores have computerized testing equipment to help you monitor these factors as well as others (cyanuric acid, metals, etc.). Ask your pool builder or applicator for a location near you.

PEBBLE TECHNOLOGY INC

15540 N 77th ST

Visit us on the web at www.pebbletec.com

SCOTTSDALE, AZ 85260-1739

SAMPLE